

P900 AIR PURIFIER

| | |
|--------------|--|
| Project name | |
| Architect | |
| Engineer | |
| Purchaser | |
| Submitted by | |

| | | | | | | |
|----------|--|---------|-------------|----------|---------|---------|
| Quantity | | Unit(s) | Designation | PORTABLE | Model : | P900 GX |
|----------|--|---------|-------------|----------|---------|---------|

TYPE: PORTABLE AIR PURIFIER

Standard Features

| | |
|---|---|
| Dimensions: | |
| Outside dimensions (in) | 3.91 (9.93 cm), 11.66 (29.61 cm), 18.66 (47.40 cm) |
| Air inlet/Air outlet | 2.5 (49.7 cm), 7 (3.49 cm) / 3.5 (8.89 cm), 7.5 (19.05cm) |
| Shipping weight | 11.0 lbs (5 kg) |
| Power | 120 volt /230 v |
| Watts/Amps | 85 Watts // .220 a (120v) .111 a (230v) |
| Control | Touch sensitive PAD-on/off, speed control timer |
| Accessories | Steel stand, carry-on handle, built in hanging hole |
| Air flow under load | 40-75 cfm |
| UV lamp tye | Proprietary regular Intensity 19mm mercury vapor quartz |
| UV Wavelength in nanometers(nm) | 254nm UVC/ 185nm UVV-one(1) inch splice |
| UV Lamp configuration | one (1) "J" shaped |
| Lenght of lamp | 6.5 in (16.5 cm) |
| Internal Lumina coating to prevent solarization | Yes |
| Reflector | Anodized aluminum box/lamp parralel to airflow |
| Lamp change out time | 17,000 hours |
| Lamp warranty | 2 years |
| Ballast / motor warranty | Balast 3 years / motor 1 year |
| Construction | Steel/Powder coated paint |
| Certifications | ETL - CSA C22.2# 113 Issued- UL 507 lissued |
| Lamp (part number) | LMPRGXJ65 |
| Ballast -voltage- (part number) | BST120/240GL |

