

VP900 AIR PURIFIER

| | |
|--------------|--|
| Project name | |
| Architect | |
| Engineer | |
| Purchaser | |
| Submitted by | |

| | | | | | | |
|----------|--|---------|-------------|-------------|---------|-------|
| Quantity | | Unit(s) | Designation | INTERCEPTOR | Model : | VP900 |
|----------|--|---------|-------------|-------------|---------|-------|

TYPE: EMERGENCY VEHICLE AIR PURIFIER

Standard Features

| | |
|---|---|
| Dimensions: | |
| Outside dimensions (in) | 4.622 (11.74 cm), 10.75 (27.3 cm), 17 (43.18 cm) |
| Air inlet/Air outlet | 2.5 (49.7 cm), 7 (3.49 cm) / 3.5 (8.89 cm), 7.5 (19.05cm) |
| Shipping weight | 7.95 lbs (2.97 kg) |
| Power | 12volt |
| Watts/Amps | 22.2 Watts //1.85a |
| Control | on/off rocker switch |
| Cord | 5 feet with 12V cigarette lighter plug |
| Air flow under load | 40-75 cfm |
| UV lamp tye | Proprietary regular Intensity 19mm mercury vapor quartz |
| UV Wavelength Nanometers(nm) | 254nm UVC |
| UV Lamp configuration | one (1) "J" shaped |
| Longueur de la lampe UV | 6.5 in (16.5 cm) |
| Internal Lumina coating to prevent solarization | Yes |
| Reflector | Anodized aluminum box/lamp parralel to airflow |
| Lamp change out time | 17,000 hours |
| Lamp warranty | 2 years |
| Ballast / motor warranty | Balast 3 years / motor 1 year |
| Construction | Aluminum /Powder coated paint |
| Color | Beige |
| Lamp (part number) | LMPRGJ65 |
| Ballast -voltage- (part number) | BST120/240GL |



